

Balex-40

Cross cylinder balers

GEUROPRESS



A superior range of remotely adjustable vertical balers with SMART technology to meet almost any demand for waste handling.

Benefits & features

- Bale fits on a EUR pallet •
- Integrated bale strap cutting blade
- Sizeable feed opening
- Spacious chamber, easily compacts • even large cardboard boxes
- Strap mount on the front •
- Key-operated lock switch
- Clear instructions for operation on front panel
- Safe and easy-to-use handle
- Safe two-hand bale ejection
- Separate program for plastic
- Quiet operating sound •
- Fast cycle saves time
- 'Bale full' light when bale is finished
- SMART functions
- 24-month warranty

Europress Balex[®] is the answer to the demand for a high-quality Nordic baler. Balex balers are designed and manufactured in Finland at the Europress factory in Kerava. The sturdy machines can withstand heavy duty use. Balex balers represent Finnish innovation at its finest.

Balex balers are part of the Europress SMART baler family. Smart balers save costs and energy and are very environmentally friendly compared to traditional balers. Due to the intelligent SMART technology, they are resistant to wear and tear, causing less down-time in daily operation.

Balex-40 is perfect for small spaces and various materials. It operates quietly and boasts large feed opening. The design of the device has taken into account all effective and upcoming EU standards and amendments with regard to device safety.

Product information

Model

Compaction force (t) Baler dimensions H x W x D (mm) 1,995 x 1,810 x 1,250 Baler weight (kg) Feed opening H x W x D (mm) Feed height (mm) Bale dimensions H x W x D (mm) Bale weight (kg) (cardboard) Power supply

Cycle time (s) Noise level (dBa) Motor

40 2.060 520 x 1,120 x 950 940 950 x 1,200 x 840 350-400 400 V, 50 Hz, 3x 16 A Slow blow fuse 61 59 4.0 kW

Balex-40





EMAIL

sales@kenburn.co.uk

www.kenburn.co.uk



UK Distributor: Kenburn Waste Management Limited Porters Wood, St Albans, Hertfordshire, AL3 6HX Tel. 01727 844 988