

Mobile-Pack-Bin MPB 918-SN

with self-cleaning BERGMANN system. No regular cleaning under and behind the piston required, equipped for roll-on roll-on roll-off vehicles, particularly suitable for <u>wet waste and problematic waste.</u>

Technical Details:

* Integrated hydraulic unit that can be pulled out to the side

* compaction system: self-cleaning pendulum piston

* Continuously loadable - in each press piston position there is always a constant large filling volume available

* no blocking during the press stroke

* Press section and container space are welded in one piece from the filling edge to the backdoor

* The pendulum flap is locked twice and additionally equipped with two toggle closures

* The special design of the container guarantee an easy empty

Standard equipment of machine:

fold down front hook, hook height can be adjusted to 1.450 mm or 1.570 mm

* manoevring hook at rear welded on a height of 1.570mm

* pendulum discharge door, secure galvanized double locking device

* plastic rollers in front and at rear

* conical container

* single pump

* oil deficiency switch

* from outside greasable cylinder hinges


* electrical connection via 32A-CEE-plug (16A-CEE-plug or additional phase inverter optional)

* automatic switch off after running time

* lockable lateral control panel on the right side (remote control optional)

* two-component coating (80 µm) in RAL colour as requested

= =	1760 -	A D	
2240 2085 1450 / 1570	·		1450 / 1570
		 с В	
⊢- ⊺€		P	
2102 1800	+++		
2 			
	1080		



		Stand: 07.01.2022	Index: 003		All indicated dimensions are approximate dimensions! Subject to technical modifications!							
Power: Fuse protection Electrical connection:	5,5 kW C 25A 400V, 50Hz, clockwise	Type:	capacity [m³]	maximum operating pressure [bar]	theoretical cylinder thrust [kN]	theoretical blade face pressure [N / cm²]	net weight [kg]	max. total weight [kg]	" A " [mm]	" B " [mm]	" C " [mm]	" D " [mm]
Forward / return cycle speed:	14 s. / 15 s.	MPB 918-SN/14	14	230	361	35,8	4.300	9.900	5.150	4.955	4.745	2.760
Displaced volume:	0,75 m³	MPB 918-SN/18	18	250	393	39,0	4.500	11.700	5.900	5.705	5.495	3.510
Capacity charge box:	2,5 m³	MPB 918-SN/20	20	250	393	39,0	4.675	12.675	6.350	6.155	5.940	4.000
		MPB 918-SN/22	22	250	393	39,0	4.850	13.650	6.790	6.595	6.385	4.400